



BC228

—
KNUCKLE BOOM CRANE

BOWMAN CRANE &



XCMG XUZHOU
TRUCK-MOUNTED
CRANE Co.,Ltd.

TABLE OF MAIN TECHNICAL PARAMETERS

ITEM	BC228-1	BC228-2	BC228-3	BC228-4
momento massimo di sollevamento / max. lifting moment / momento máximo de elevación / couple de levage maximum / Max. Hubmoment	21.9 tm	21.5 tm	21.2 tm	21.0 tm
massima capacità di sollevamento / max. lifting capacity / maxima capacidad de levantamiento / meilleure capacité de soulèvement / Max. Hubkraft	10000kg	10000kg	10000kg	10000kg
massimo sfilo idraulico / max. hydraulic outreach / max. alcance hidraulico / rallonge hydraulique max. max. hydraulische reichweite	6460mm	8540mm	10640mm	12750mm
portata pompa consigliata / recommended pump delivery / caudal bomba aconsejada / debit d'huile recommandé Förderleistung der Hydraulikpumpe	40 L/min	40 L/min	40 L/min	40 L/min
pressione di lavoro / working pressure / presión de trabajo / pression de travail / Betriebsdruck	30Mpa	30Mpa	30Mpa	30Mpa
capacità serbatoio / tank capacity / contenance du reservoir / capacidad deposito de aceite / Inhalt des Öltanks	100L	100L	100L	100L
angolo di rotazione / slewing angle / angulo de giro / angle de rotation / Schwenkbereich	410°	410°	410°	410°
coppia di rotazione / slewing torque / momento de giro / couple de rotation / Drehmoment	42.9 kNm	42.9 kNm	42.9 kNm	42.9 kNm
peso gru completa di stabilizzatori estensibili e martinetti piedi / crane weight including side extensions and rams of stabilizers / peso de la grua incluidos las extensiones y los cilindros de los estabilizadores / poids grue complète de bequilles extensibles et verins stabilisateurs / Eigengewicht, einschl-manuell seitlich ausziehbare Abstützungen	2745kg	2930kg	3080kg	3210kg

